

Hamamatsu Orca Flash 4.0 C11440 with Camera Link Interface

Slow Scan					Standard Scan				
ROI	Row Offset	Max FPS	Min Exposure (ms)	Max Exposure (ms)	ROI	Row Offset	Max FPS	Min Exposure (ms)	Max Exposure (ms)
2048x2048	0	30	3.0208	33.33	2048x2048	0	100	1.0037	9.99
2048x1024	512	60	3.0208	16.63	2048x1024	512	200	1.0037	4.98
2048x512	768	120.3	3.0208	8.24	2048x512	768	400	1.0037	2.48
2048x256	896	240.7	3.0208	4.09	2048x256	896	800	1.0037	1.23
2048x128	960	474	2.0788	2.0788	2048x128	960	1580	0.6236391	0.6236391
2048x64	992	932	1.0394	1.0394	2048x64	992	3100	0.3118195	0.3118195
2048x32	1008	1800	0.5196992	0.5196992	2048x32	1008	6036	0.1559	0.1559
2048x16	1016	3420	0.2598496	0.2598496	2048x16	1016	12823	0.0779549	0.0779549
2048x8	1020	7697	0.1299248	0.1299248	2048x8	1020	20543	0.0389774	0.0389774
2048x4	1022	7697	0.1299248	0.1299248	2048x4	1022	20543	0.0389774	0.0389774