

Hamamatsu Orca Flash 4.0 C11440 with Camera Link Interface			Hamamatsu Orca Flash 4.0 C11440 with Camera Link Interface			Hamamatsu Orca Flash 4.0 C11440 with Camera Link Interface			Hamamatsu Orca Flash 4.0 C11440 with Camera Link Interface		
Frame Size: 2048x256			Frame Size: 2048x256			Frame Size: 2048x256			Frame Size: 2048x256		
Row Offset	Slow Scan Speed (FPS)	Standard Scan Speed (FPS)	Row Offset	Slow Scan Speed (FPS)	Standard Scan Speed (FPS)	Row Offset	Slow Scan Speed (FPS)	Standard Scan Speed (FPS)	Row Offset	Slow Scan Speed (FPS)	Standard Scan Speed (FPS)
0	120	400	448	120	400	896	240	802	1340	120	400
8	120	400	460	120	400	900	233	777	1348	120	400
20	120	400	468	120	400	908	220	732	1360	120	400
28	120	400	480	120	400	920	202	673	1368	120	400
40	120	400	488	120	400	928	192	640	1380	120	400
48	120	400	500	120	400	940	179	596	1388	120	400
60	120	400	508	120	400	948	170	570	1400	120	400
68	120	400	520	120	400	960	160	534	1408	120	400
80	120	400	528	120	400	968	153	512	1420	120	400
88	120	400	540	120	400	980	145	484	1428	120	400
100	120	400	548	120	400	988	139	466	1440	120	400
108	120	400	560	120	400	1000	132	442	1448	120	400
120	120	400	568	120	400	1008	128	427	1460	120	400
128	120	400	580	120	400	1020	122	407	1468	120	400
140	120	400	588	120	400	1028	120	400	1480	120	400
148	120	400	600	120	400	1040	120	400	1488	120	400
160	120	400	608	120	400	1048	120	400	1500	120	400
168	120	400	620	120	400	1060	120	400	1508	120	400
180	120	400	628	120	400	1068	120	400	1520	120	400
188	120	400	640	120	400	1080	120	400	1528	120	400
200	120	400	648	120	400	1088	120	400	1540	120	400
208	120	400	660	120	400	1100	120	400	1548	120	400
220	120	400	668	120	400	1108	120	400	1560	120	400
228	120	400	680	120	400	1120	120	400	1568	120	400
240	120	400	688	120	400	1128	120	400	1580	120	400
250	120	400	700	120	400	1140	120	400	1588	120	400
260	120	400	708	120	400	1148	120	400	1600	120	400
270	120	400	720	120	400	1160	120	400	1608	120	400
280	120	400	728	120	400	1168	120	400	1620	120	400
288	120	400	740	120	400	1180	120	400	1628	120	400
300	120	400	748	120	400	1188	120	400	1640	120	400
308	120	400	760	120	400	1200	120	400	1648	120	400
320	120	400	768	120	400	1208	120	400	1660	120	400
328	120	400	780	126	420	1220	120	400	1668	120	400
340	120	400	788	130	434	1228	120	400	1680	120	400
348	120	400	800	137	459	1240	120	400	1688	120	400
360	120	400	808	142	475	1248	120	400	1700	120	400
368	120	400	820	150	503	1260	120	400	1708	120	400
380	120	400	828	157	523	1268	120	400	1720	120	400
388	120	400	840	167	558	1280	120	400	1728	120	400
400	120	400	848	174	582	1288	120	400	1740	120	400
408	120	400	860	187	625	1300	120	400	1748	120	400
420	120	400	868	197	658	1308	120	400	1760	120	400
428	120	400	880	213	713	1320	120	400	1768	120	400
440	120	400	888	226	754	1328	120	400	1780	120	400